



Flow Characteristics Chart
HKD SV6201, SV4400, SX4400

| | Colder ← | ↔ | → | Warmer |
|---------------------------------|---------------------|---------------------|---------------------|---------------------|
| Top (2) Nozzle Types | 2540 | 2530 | 2520 | 2515 |
| Bottom (2) Nozzle Types | 2540 | 2530 | 2520 | 2515 |
| Water Pressure (PSI) | Flow GPM | Flow GPM | Flow GPM | Flow GPM |
| 180 | 35 | 27 | 19 | 14 |
| 200 | 37 | 28 | 20 | 15 |
| 220 | 39 | 30 | 21 | 16 |
| 240 | 41 | 31 | 22 | 17 |
| 260 | 42 | 33 | 23 | 18 |
| 280 | 44 | 34 | 24 | 18 |
| 300 | 46 | 35 | 24 | 19 |
| 320 | 47 | 36 | 25 | 20 |
| 340 | 49 | 37 | 26 | 20 |
| 360 | 50 | 39 | 27 | 21 |
| 380 | 52 | 40 | 28 | 22 |
| 400 | 53 | 41 | 28 | 22 |
| 420 | 55 | 42 | 29 | 23 |
| 440 | 56 | 43 | 30 | 23 |
| 460 | 57 | 44 | 30 | 24 |
| 480 | 58 | 45 | 31 | 24 |
| 500 | 60 | 46 | 32 | 25 |
| 520 | 61 | 47 | 32 | 25 |
| 540 | 62 | 48 | 33 | 26 |
| 560 | 63 | 48 | 34 | 26 |
| 580 | 64 | 49 | 34 | 27 |
| 600 | 66 | 50 | 35 | 27 |
| 620 | 67 | 51 | 35 | 28 |
| 640 | 68 | 52 | 36 | 28 |
| 660 | 69 | 53 | 37 | 29 |
| 680 | 70 | 54 | 37 | 29 |
| 700 | 71 | 54 | 38 | 29 |
| 710 | 71 | 55 | 38 | 30 |