



Flow Characteristics Chart HKD SV6400 / SX6400

	Colder Configuration				Moderate Configuration				Warmer Configuration			
Nozzle 1	2530	2530	2530	2530	2520	2520	2520	2520	2515	2515	2515	2515
Nozzle 2	2530	2530	2530	2530	2520	2520	2520	2520	2515	2515	2515	2515
Nozzle 3	2530	2530	2530	2530	2520	2520	2520	2520	2515	2515	2515	2515
Nozzle 4	2530	2530	2530	2530	2520	2520	2520	2520	2515	2515	2515	2515
Nozzle 5 (valve 1)	OFF	2540	OFF	2540	OFF	2530	OFF	2530	OFF	2520	OFF	2520
Nozzle 6 (valve 2)	OFF	OFF	2560	2560	OFF	OFF	2540	2540	OFF	OFF	2530	2530
Water Pressure (PSI)	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM
180	24	33	37	45	16	22	24	31	12	16	18	22
200	26	34	39	47	17	24	26	32	13	17	19	24
220	27	36	41	50	18	25	27	34	14	18	20	25
240	28	38	43	52	19	26	28	36	14	19	21	26
260	30	40	45	55	20	27	30	37	15	20	22	27
280	31	41	46	57	21	28	31	39	15	21	23	28
300	32	43	48	59	21	29	32	40	16	21	24	29
320	33	44	50	61	22	30	33	41	17	22	25	30
340	34	46	51	63	23	31	34	43	17	23	26	31
360	35	47	53	65	24	32	35	44	18	24	26	32
380	36	48	54	67	24	33	36	45	18	24	27	33
400	37	50	56	68	25	34	37	47	19	25	28	34
420	38	51	57	70	25	35	38	48	19	25	29	35
440	39	52	59	72	26	36	39	49	20	26	29	36
460	40	53	60	73	27	37	40	50	20	27	30	37
480	41	55	61	75	27	38	41	51	20	27	31	38
500	42	56	63	77	28	38	42	52	21	28	31	38
520	43	57	64	78	28	39	43	53	21	28	32	39
540	43	58	65	80	29	40	43	54	22	29	33	40
560	44	59	66	81	30	41	44	55	22	30	33	41
580	45	60	68	83	30	41	45	56	23	30	34	41
600	46	61	69	84	31	42	46	57	23	31	34	42
620	47	62	70	86	31	43	47	58	23	31	35	43
640	47	63	71	87	32	43	47	59	24	32	36	43
660	48	64	72	88	32	44	48	60	24	32	36	44
680	49	65	73	90	33	45	49	61	24	33	37	45
700	50	66	75	91	33	46	50	62	25	33	37	46
710	50	67	75	92	33	46	50	63	25	33	38	46